

Line protocol handler

The Line protocol handler parses simple text lines.

Important: Each line must end with a newline! Especially important when not using a file for input but e.g. [TCP Server transport handler](#) or [AMQP / RabbitMQ transport handler](#).

Options

- **delay:** Delay of reading in milliseconds (default 0). DEPRECATED: use `scheduler.delay` instead if not used together with `delayeach`
- **nanodelay:** Delay of reading in nanoseconds (default 0).
- **delayeach:** The number of lines between a delay is used (default 0).
- **checkdelay:** Delay between reading attempts when the transport stream isn't ready. Useful for polling log files which are currently written to reduce I/O overhead (default 0).
- **readfirstline:** Should the first line of the file be ignored (e.g. because of header information) (default: true)
- **skipFirstLines:** The number of lines that should be skipped. Use this, if one or more lines should be skipped (e.g. in case of a longer header).
- **debug:** If set to true, some additional things are available: (default false)
 - **dumpEachLine:** Dumps lines to the console. if set to 1 each line will be dumped
 - **measureEachLine:** Measures the processing time between n elements that are dumped
 - **maxLines:** Stop processing after n elements are read

Example

PQL

Line Protocol Handler

```
input = ACCESS({source='Line', wrapper='GenericPush',
transport='File', protocol='Line',
  dataHandler='Tuple', options=[['filename', 'test.csv'], ['delay', '100']],
  schema=[
    ['line', 'String'] ]
})
```

CQL