

Mosaik protocol handler

The mosaik protocol handler can be used to access data from the Smart Grid co-simulation framework [mosaik](#).

To connect odysseus and mosaik, the odysseus query has to run first and after that the simulation in mosaik can be started.

In the mosaik documentation a [tutorial](#) can be found which describes the connection between mosaik and odysseus.

Options

- **cleanStrings** If set to true, all underscores (_) in attribute names are replaced by hyphen (-), so that they can be used in expressions.

Example

PQL

MosaikProtocolHandler

```
mosaik = ACCESS({TRANSPORT = 'TCPServer',
                  PROTOCOL='Mosaik',
                  SOURCE = 'Mosaik',
                  DATAHANDLER = 'KeyValueObject',
                  WRAPPER = 'GenericPush',
                  OPTIONS =[
                      ['port', '5555'],
                      ['mosaikPort', '5554'],
                      ['byteorder', 'LITTLE_ENDIAN']
                  ]})

///short version:
mosaikInput = MOSAIK({source = 'MosaikReceiver',
                      type = 'simapi'})
///
                      type = 'zeromq'})
```

Simulator in mosaik

To allow the connection in mosaik a simulator has to be created as follows:

Initialising mosaik simulator

```
sim_config = {'Odysseus':
              {'connect': '127.0.0.1:5554' }
}

odysseusModel = world.start('Odysseus', step_size=60*15)
odysseus = odysseusModel.Odysseus.create(1)
```

To receive data components have to be connected to the simulator in the mosaik scenario definition.

In the mosaik-demo this could be:

Connecting mosaik simulator

```
connect_many_to_one(world, nodes, odysseus[0], 'P', 'Vm')
connect_many_to_one(world, houses, odysseus[0], 'P_out')
connect_many_to_one(world, pvs, odysseus[0], 'P')
```

More details can be found in the mosaik [documentation](#).