

Command

These functions can be used with the [Command Operator](#).

AddQuery

Allows to send a new query to the system.

- String: QueryText
- String: Parser

```
addQuery("data = ACCESS(...)", "PQL")
```

FullQuery

A query can have different [Query States](#). This function set the query with the given ID or name to full mode.

- fullQuery(queryID)
- fullQueryByName(queryName)

PartialQuery

A query can have different [Query States](#). This function set the query with the given ID or name to partial mode.

- partialQuery(queryID)
- fullQueryByName(queryName)

RemoveQuery

Remove query with the given query id or name.

- removeQuery(queryID)
- removeQueryByName(queryName)

ResumeQuery

A query can have different [Query States](#). This function set the query with the given ID or name to resume mode.

- resumeQuery(queryID)
- resumeQueryByName(queryName)

SetPeriod

Update the period (e.g. in a timer source).

```
setPeriod("MyTimer.transport",1000.0))
```

StartQuery

Start query with the given query id or name.

- startQuery(queryID)
- startQueryByName(queryName)

StopQuery

Stop query with the given query id or name.

- stopQuery(queryID)
- stopQueryByName(queryName)

SuspendQuery

A query can have different [Query States](#). This function set the query with the given ID or name to suspend mode.

- `suspendQuery(queryID)`
- `suspendQueryByName(queryName)`